

Contact Interface flush-mount – 6 channels

Product ref.: 153501A0



Technical specifications

Supply voltage	2x 1.5 V LR03/micro/battery
Battery life	3 years (typ.)
Degree of protection	IP20
Ambient temperature	5 to 35 °C
Dimensions (W x H x D)	48.5 x 53 x 15 mm
Weight	50 g (including batteries)
Radio frequency band	868.0-868.6 MHz 869.4-869.65 MHz
Typ. open area RF range	230 m



Product features

- For retrofitting of conventional floating push-buttons with 6 push-buttons, for example, to enable smart and individual wireless control
- Integration of switches, push-buttons or contacts into the Homematic IP system for controlling e.g. lights or shutters
- Easy installation thanks to battery operation – no connected to the power supply needed
- Compact housing for installation into standard flush-mounted boxes – in combination with deep boxes even behind existing switching elements
- Offers comfortable integration while existing switches and switch systems can continue to be used
- To enable operation, the device has to be connected with one of the following solutions:
 - Homematic IP Access Point with free smartphone app and free cloud service
 - Central Control Unit CCU2/CCU3 with local user interface WebUI
 - Third-party solutions of partners

Logistical data

Product reference	153501A0
EAN code	4047976535019
Short description	HmIP-FCI6
Packing unit	144
Packing dimensions	122 x 93 x 36 mm
Weight incl. packaging	107.5 g

Package contents

Homematic IP Contact Interface flush-mount – 6 channel

Connecting cable

1.5 V LR03/micro/AAA batteries (2x)

User manual