

START NOW!

**REDUCE HEATING
COSTS, INCREASE
YOUR COMFORT**


Starter set Climate Control – WLAN

HmIP-SK12

The easy way into smart heating control: Time-controlled heating and detection of open windows during ventilation can save up to 30% of valuable energy. The heart of the smart home is formed by the flexible WLAN Access Point. It is simply connected to the wireless network via the Homematic IP app.



homematic 
Smart Living, Simply Exciting.



Individual heating profiles via the free Homematic IP app



EASY WAY INTO THE SMART HOME WORLD

Flexible extension to a comprehensive smart home is possible at any time thanks to the large Homematic IP product range.

TECHNICAL SPECIFICATIONS

WLAN Access Point

Supply voltage	Power supply unit (5 Vdc)
Dimensions (W x H x D)	100 x 40 x 19 mm
Typical open area RF range	250 m

Radiator Thermostat:

Supply voltage	2x 1.5 V LR6/mignon/AA
Battery life	2 years (typ.)
Dimensions (W x H x D)	57 x 68 x 102 mm
Typical open area RF range	250 m
Threaded connection	M30 x 1.5 mm

Window / Door Contact:

Supply voltage	2x 1.5 V LR03/micro/AAA
Battery life	4 years (typ.)
Dimensions (W x H x D)	102 x 18 x 25 mm (electronic unit) 48 x 11 x 13 mm (magnetic contact)
Typical open area RF range	200 m

For further technical details and information, please refer to the data sheet of the respective device.

COMFORT TEMPERATURE AT ALL TIMES

The room temperature is controlled according to the individual needs of the user: simply via app, whether at home or on the road, directly on the device or conveniently via voice control (via Amazon Alexa or Google Assistant).

SAVES HEATING COSTS

Individual temperature profiles can easily be created via the app – with up to 3 configurable heating profiles and 13 changes per day. In this way, the heating is switched on only if needed.

MONITORING OF WINDOWS AND DOORS

Open windows and doors are detected by the window / door contact. The room temperature is immediately reduced to avoid any waste of energy. The individual comfort temperature is automatically set as soon as the window is closed.

COMFORTABLE AND SECURE, ALSO WHILE BEING ON THE WAY

The Homematic IP app is used to adjust the personal temperature at any time – even when you are out and about, in case you get home earlier than expected.

The app immediately displays open windows and doors so you have everything in sight.

MANY ADDITIONAL FUNCTIONS

- ✓ Boost function: quick heating of rooms
- ✓ Eco mode: energy-saving operation with reduced room temperature
- ✓ Valve protection function: protects against calcification
- ✓ Operating lock: against unintended operation

LOGISTICAL DATA

Product reference	155694A0
EAN code	4047976556946
Short description	HmIP-SK12
Packing unit	18
Packing dimensions	185 x 280 x 97 mm
Weight incl. packaging	696.3 g

PACKAGE CONTENTS

Homematic IP WLAN Access Point (including plug-in mains adapter)
 Homematic IP Radiator Thermostat – basic (incl. Danfoss adapter RA)
 Homematic IP Window / Door Contact with magnet
 Batteries
 Mounting accessories
 User manual